



Technical Data sheet

Extra strong paint remover

For Wood

Code 0031-ES and 0034-ES



DESCRIPTION

Removes all types of paints, including two-pack polyurethanes. Complies with European safety standards.

Available liquid (Cod 0031-ES) or gel (Cod 0034-ES). The gel version is particularly suitable for vertical surfaces. Contains no methylene chloride, no it is corrosive and does not alter the color of the wood.

FIELDS OF APPLICATION

Exterior wood constructions such as: log houses, siding, enclosed porches, wood windows, entry and garage doors, balconies, shutters, fences, pergolas, etc. Inside - wooden ceilings, wainscoting and other structural or cladding elements.

Characteristics	UM	Value
Appearance		liquid or gel
Colour		colorless
Odour		characteristic
pH		6.8 ± 0.1



HOW TO USE



Apply evenly creating a consistent layer of material (2-3mm).



Leave for 15-30 minutes.



Scrape with a spatula or steel wool. Remove the residues with a cloth soaked in [Shellac 99](#) or [DFP50](#).



Clean the treated surface with a soft cloth soaked in alcohol. If necessary, repeat the operation.

TECHNICAL RECOMMENDATIONS

Shake before using.

Open carefully.

Do not apply in direct sunlight, on hot surfaces, in the presence of strong wind, rain, fog or with the risk of freezing at night.

Always carry out a preliminary test on a small area to check if the effect is as desired.

On surfaces previously treated with other products it is necessary to perform a light sanding to improve adhesion and an application test to verify compatibility.

PACKING

Gel

0031-ES	6 x 750mL
0032-ES	2 x 4 litres
0033-ES	1 x 20 Lt

Liquid

0034-ES	6 x 750mL
0036-ES	2 x 4 litres
0038-ES	1 x 20 Lt

STORAGE

Keep in a cool and well-ventilated place. Keep the jar tightly closed when not in use.

Keep away from heat, flames, sparks and other fire sources.

The product has a shelf life of 24 months from the production date.

WARNING

Read the safety data sheet before use.

Observe the safety regulations in force.

Product for professional use.

Our technical sheets are prepared based on average results of our tests. However, our technical advice is given in good faith but without guarantee. In fact, different supports, application conditions, instruments, dilution ratio are an integral part of the final result and often beyond any control. The user must test the supplied products in order to see if they are suitable for his needs. On our part we guarantee the continuity of the chemical and physical characteristics.

Product code: **0031-ES and 0034-ES**
Revision: **01 of 10.07.2023**



Exterior Line
TRADITIONAL TECH.



BORMA WACHS[®]
Wood Professional Cosmetics

Extra Strong Paint Remover p. 3of 3

BPS srl - Via Industria, no. 4 - 30029 S. Stino di Livenza (Venice) - Italy
Tel.: +39 0421 951900 Fax.: +39 0421 951902 www.bormawachs.com email: info@bormawachs.it