



Technical data Sheet

REV 00 of 20.10.2012

ECOSTUCCO

Waterborne Wood Filler

DESCRIPTION:

Ecostucco, is a hydro-putty formulated and composed of first quality raw materials. It is particularly suitable for wood and plastering and scraping wall surfaces before painting and varnishing.

The product is ready for use, and should be applied with a spatula directly on the defect to be filled.

It dries quickly and remains unaltered (colours are light resistant). Among it's main characteristics are: easily sand-papered, limited loss, good anchorage with minimum absorption.

CHEMICAL/PHYSICAL CHARACHTERISTICS:

Form at 20°C: Paste

Available colors: Pine, Ash, Oak, Cherry, Douglas, Natural wood,

Chestnut, Teak, Mahogany, Light Walnut,

Medium Walnut, Dark Walnut, Beech.

Color :PigmentedOdor :OdourlessDilution:Water

Drying time: 6/8 hours with normal moisture. Possible over-

lacquering after 24 hours.

HOW TO USE:

- Apply the product directly on the wood surface
- Let it dry for approx 6/8 hours
- Sand the excess.
- After approx 24 hours, depends from the climate, moisture, dimension of the defect, stain or varnish as required.
- All technical equipments, can be easily cleaned with hot water.

STORAGE:

Store in closed storing places with a temperature not below 5°C and over 35°C. After use keep containers tightly closed. Do not allow the product to dry.

PACKAGING:

The product comes in 250 gr., 500 gr., 1 Kg, 5 Kg plastic cans.



WARNING:

Our technical sheets are complied on the bases of results of our tests. Nevertheless our technical advice is given in good faith, but without a guarantee. Indeed different supports, conditions, applications, installations, dilutions are integrating parts of the final result and often beyond every control. The user must test the supplied products to verify if it is adaptable for his/her needs.

We can guarantee the continuity of the physical and chemical characteristics.