



Technical Data Sheet

REV 00 of 20.10.2012

SAUNA OIL

Protection for Benches in Steam Rooms

DESCRIPTION:

Borma SAUNA OIL is a blend of oils suitable for the treatment of the benches in steam rooms, as well as steam room walls and floor, made of raw wood. Thanks to its composition, naturally enhances color and veins of the wood, and gives a good protection against moisture.

PHYSICAL - CHEMICAL CHARACTERISTICS:

Form: Liquid
Color: Colorless
Odour: Odourless
Density: 0,85 Kg/Lt

Drying time: 24 / 48 depending on wood absorption, air exchange,

temperature

Yield: 8 – 15 m²/Lt depending on wood absorption

Solid Content: About 100% **Temperature of application:** > +5°C

Humidity of application: Relative humidity <80%

HOW TO USE:

The product is ready to use, especially on raw wood.

Clean and degrease the surface to be treated. If the bench has been already treated and is deteriorated, sand with sandpaper 220 grit.

On a dry and clean bench, apply SAUNA OIL by brush or by cotton cloth and let the wood absorb the oil. The operation can be repeated in case of very porous wood.

PACKAGE:

The product comes in 500ml, 1Lt and 5Lt sized cans.

STORAGE:

Store in a cool, well ventilated place, and keep the container closed when not in use. Keep from freezing.

WARNING

Our data sheets are prepared on the basis of average performance of our tests. However, our technical advices are given in good faith but without any warranty. In fact different supports, conditions of application, industrial plants, dilutions are determinant for the final result, and are often beyond our control. The user must try the product to see if it is suitable for his needs. We will ensure the continuity of the chemical-physical characteristics.